

## EF-2C

### Rechargeable Utility Flashlight

The DME EF-2C is a high intensity, hand-held rechargeable flashlight with mounting bracket that is easily installed on walls, bulkheads and partitions in aircraft; marine vessels, wheel and tracked vehicles, and buildings.



#### Power Source

- Nickel metal hydride battery pack

#### Part Numbers

##### Description

- Model EF-2C, 28VDC
- Model 316 Battery Pack

##### Part Number

- P2-07-0009-520
- P4-01-1003-001

#### System Size and Weight

10.125 in L x 2.75 in W x 3.00 in H  
(257.2 mm L x 69.85 mm W x 76.2 mm H)

1.25 lbs (.57 kg) nominal

#### Specifications

- Light operating time: 120 minutes per charge
- Light output: approximately 1,150 candela
- Operating temperature: -40 °C to 70 °C (-40 °F to 158 °F)

#### Certification

FAA-PMA (28VDC)

#### KEY BENEFITS

- Constructed with ABS flame retardant material, the EF-2C conforms to FAR 25.853(a), FAR 121.549(b), FAR 121.310(n) and applicable SAE, ATA, Boeing/Airbus OEM specifications and military specifications.
- Waterproof
- Rechargeable
- Floats, beam-up
- Self-cleaning switch
- Charge status indicator
- System includes rewritable RFID tag

#### ORDERING INFO

130 Commerce Way  
East Aurora, NY 14052 USA  
+1.716.655.0800  
LSINYSales@astronics.com  
[astronics.com/emergencysystems](http://astronics.com/emergencysystems)